

SPECIFICATIONS

RCC

EARTHQUAKE RESISTANCE STRUCTURE DESIGN FOR LONG LIFE OF BUILDING

WALLS

EXTERNAL DOUBLE COAT PLASTER & WATER RESIST' TEXTURE WITH ACRYLIC PAINT
INTERIOR WALA PLASTER (WITH PUTTY FINISH)

DOORS AND WINDOWS

DECORATIVE MAIN DOOR WITH GRANITE FRAME
INTERNAL FLUSH DOORS
FULLY ANODIZED ALUMINIUM SLIDING WINDOWS WITH GRANITE SEAL

FLOORING

VITRIFIED FLOORING IN DRAWING, DINNING, BEDROOMS AND KITCHEN
RUSTIC TILES IN BALCONY
GRANITE IN STAIRCASE

KITCHEN

GRANITE PLATFORM
TILES DAQD UP TO LINTEL LEVEL
FULL BODY VITRIFIED TILES IN WASH AREA

BATHROOM

DESIGNER TILES IN ALL TOILETS UP TO LINTEL LEVEL
BRANDED BATH FITTING
STANDARD QUALITY OF SANITARY WARE
OVERHEAD P/C WATER TANK

ELECTRIFICATION

CONCEALED COOPER WIRING WITH MODULAR SWITCHES
ADEQUATE POWER SUPPLY FROM GEB

TERRACE

CHINA MOSAIC IN TERRACE AREA FOR WATERPROOFING AND HEAT RESISTANCE

