



रेवती

SPECIFICATION

STRUCTURE	Earthquake resistant composite structure.
FLOORING	Vitrified tiles flooring in all rooms. Rustic tiles in balcony and wash. Termite treatment.
KITCHEN	Granite platform with S.S. sink. Glazed tiles dado up to lintel level and below platform. Glazed tiles dado in wash area. Chimney will be provided for exhaust and to keep kitchen fresh and well ventilated.
TOILETS	Designer wall tiles dado up to lintel level. Standard quality (equivalent to Jaquar/Plumber) C.P.fittings. Standard quality sanitary ware (equivalent to Cera). All bedrooms have modern concept of toilet - Separate dry-dry zone with separate dressing area.
DOORS	Decorative door for main entrance. Other door will be wooden frame and one side laminated flush door with brass chrome fittings.
WINDOWS	Fully glazed wooden / anodized windows with safety grill.
PLASTER	Inside double coat mala plaster with cement base lapi putty coating (ready for paint). Outside double coat sand faced plaster with water proof acrylic emulsion.
ELECTRIFICATION	Concealed copper three phase wiring with sufficient electrical points in all areas. Standard quality ISI copper wire. Modular switch, modular board. Distribution board with miniature breakers to ensure safety. A.C. piping fitting will be provided in all bedrooms.
WATER SUPPLY	Bore well with hydro pneumatic pressure system for 24hours water supply. Solar water heater point will be provided at terrace.
TERRACE	China mosaic flooring to ensure water proofing and reduce heat transfer.