

જિલ્લા કલેક્ટરની કચેરી,
સુભાષભ્રીજ સર્કલ, આશ્રમ રોડ,
અમદાવાદ.

તા. ૦૩/૦૫/૨૦૧૬

વંચાણમાં લીધું :-

- (૧) અરજદારશ્રી બાલુજી પુંજાજી વિગેરે રહે. એ/દ, મારૂતિ નંદન વિહાર, આરેહીવીલાના ગેટમાં, બસેરા પાર્ટી પ્લોટ સામે, એસ.પી. રીંગ રોડ, બોપલ, અમદાવાદની જ.મ.કાયદાની કલમ - ૬૫ હેઠળ બીનખેતીની પરવાનગી મેળવવાની નિયત નમુનાની તા. ૧૭/૦૩/૨૦૧૬ની અરજી.
- (૨) કલેક્ટરશ્રી, અમદાવાદનો હુકમ નં. સીબી/સીટીએસ-૨/ન.શ./પ્રિમીયમ/ગોતા/સ.નં./બ્લોક નં. ૪૫૪+૪૫૫+૪૫૬/એસ.આર. ૧૭૪/૨૦૧૪/EWMS No. ૨૫૮૨, તા. ૧૬/૦૨/૨૦૧૬નો નવી અને અવિભાજ્ય શરતના નિયંત્રણો દુર કરતો હુકમ.
- (૩) અરજદારએ તા. ૧૬/૦૩/૨૦૧૬ના રોજ તત્કાલ બીનખેતી અંગેનું સોગંદનામું તથા બાંહેધરીપત્ર.
- (૪) સક્ષમ અધિકારી અને નાયબ કલેક્ટરશ્રી, શહેરી જમીન ટોચ મર્યાદા, અમદાવાદનો તા.૨૨/૦૫/૨૦૧૪નો પત્ર નં. યુ.એલ.સી./ગોતા/પ્રિમીયમ/એસ.આર. ૧૪૨/૧૪નો શ.જ.ટો.મ. સંબંધનો હકારાત્મક અભિપ્રાય.
- (૫) વધારાના ખાસ જમીન સંપાદન અધિકારીશ્રીનો તા. ૧૨/૦૪/૨૦૧૩નો પત્ર નં. એલએક્યુ/એન.એ./અભિપ્રાય/ ૫૦૦/૨૦૧૩નો સંપાદન અંગેનો હકારાત્મક અભિપ્રાય.
- (૬) બીજા વધારાના ખાસ જમીન સંપાદન અધિકારીશ્રીનો તા. ૦૫/૦૬/૨૦૧૪નો પત્ર નં. એલએક્યુ/બિ.ખે.અભિપ્રાય/ એસ.આર. ૧૦૮૮/૨૦૧૪ ગોતાનો સંપાદન અંગેનો હકારાત્મક અભિપ્રાય.
- (૭) અત્રેની કચેરીના લીગલ શાખાનો તા. ૨૮/૦૩/૨૦૧૬નો શેરા નં. એલબી/અપીલ/ગોતા-૪૫૪+૪૫૫+૪૫૬/ ૨૦૧૬/વ. ૨૮૮૮નો અપીલ/રીવીઝન અંગેનો હકારાત્મક અભિપ્રાય.
- (૮) જમીન મહેસુલ અધિનિયમ - ૧૮૭૮ની કલમ - ૬૫, ૬૬, ૬૭થી મળેલ અધિકારો તથા નિયમોના નિયમ - ૧૦૦/ ૧૦૧ મુજબ.
- (૯) સરકારશ્રીના મહેસુલ વિભાગના ઠરાવ ક્રમાંક : બખપ/૧૦૦૬/૪૨૫/ક, તા. ૧/૭/૦૮ તથા તા. ૮/૪/૧૧.
- (૧૦) સરકારશ્રીના મહેસુલ વિભાગના પરિપત્ર નં. : બખપ/૧૦૨૦૦૧૩/૭૧/ક, તા. ૧૧/૩/૨૦૧૩.

હુકમ :-

અરજદારશ્રી બાલુજી પુંજાજી વિગેરે તેઓના ખાતાની મોજે. ગોતા, તા. ઘાટલોડીયા, જી. અમદાવાદ ના સર્વે નંબર ૪૫૪+૪૫૫+૪૫૬, ટી.પી. ૫૬, ફા.પ્લોટ નં. ૧૮૮ની ૨૬૧૦૨ ચો.મી. જમીનની રહેણાંક+વાણિજ્યના હેતુ માટે બીનખેતી ઉપયોગ કરવા માટે જમીન મહેસુલ કાયદાની કલમ - ૬૫ હેઠળ પરવાનગી મેળવવા માંગણી કરેલ છે. અરજી સાથે નિયત નમુનાનું તત્કાલ એન.એ. સોગંદનામું તથા જે બાંધકામ કરવા માંગે છે તેના સુચિત પ્લાનની નકલ વિગેરે રજુ કરેલ છે.

આમુખ (૨)ના તા. ૧૬/૦૨/૨૦૧૬ના હુકમથી નવી અને અવિભાજ્ય સત્તાપ્રકારમાંથી બિનખેતીના રહેણાંકના હેતુ માટે પ્રિમીયમ વસુલવા હુકમ કરેલ છે. સદર હુકમ બીનખેતી રહેણાંકના હેતુ માટે કરવામાં આવેલ છે. જ્યારે અરજદારશ્રીએ રહેણાંક+વાણિજ્ય હેતુ માટે બીનખેતી પરવાનગીની માંગણી કરેલ છે. જેમાં ખુલ્લા પ્લોટનો જંગીનો દર મુજબ પ્રિમીયમ વસુલ લેવામાં આવેલ છે. જેથી તેમાં કોઈ તફાવત આવતો નથી.

આમુખ - (૩)થી અરજદારએ તા. ૧૬/૦૩/૨૦૧૬ ના રોજ તત્કાલ બીનખેતી અંગેનું સોગંદનામું તથા બાંહેધરીપત્ર રજુ કરેલ છે.

આમુખ - (૪) થી સક્ષમ અધિકારી અને નાયબ કલેક્ટરશ્રી, શહેરી જમીન ટોચ મર્યાદા, અમદાવાદે આ જમીનની બીનખેતી પરવાનગી આપવા અંગે રાજ્યમાંથી તા. ૩૦/૩/૧૯૮૮ના રોજથી શહેરી જમીન ટોચ મર્યાદા ધારો - ૧૯૭૬ રદ કરી રીપીલ એક્ટ - ૧૯૮૮ની જોગવાઈ લાગુ કરવામાં આવેલ છે અને કાયદો રદ થતાં તૈયાર કરવામાં આવેલ કબજે લીધેલ ફાજલ જમીનોની યાદીમાં પ્રશ્નવાળી જમીનનો સમાવેશ થતો ન હોઈ, બીનખેતીના હેતુ માટે પ્રિમીયમ નક્કી કરવામાં આવે તો યુ.એલ.સી. કાયદા અંતર્ગત વાંધાસરખું નથી તેમ હકારાત્મક અભિપ્રાય આપેલ છે.

આમુખ - (૫) અને (૬)થી સંપાદન અધિકારીશ્રીઓએ આ જમીનની બીનખેતીની પરવાનગી આપવા અંગે સદર જમીન હાલમાં સંપાદન અંગેની કોઈ કાર્યવાહી ચાલુમાં નથી કે સંપાદન હેઠળ નથી તેમ જણાવેલ છે.

આમુખ - (૭)થી અત્રેની લીગલ શાખામાં આ જમીન બાબતે હાલમાં કોઈ અપીલ / રીવીઝન અરજી પેન્ડીંગ નથી તેમ જણાવેલ છે.

ઉક્ત વિગતોએ અરજદારશ્રીની માંગણી મુજબ એપેન્ડીક્સ - એ ની જમીન બીનખેતીની પરવાનગી આપવા હસ્તક સરખું ન હોવાનું જણાયેલ છે. જેથી આ જમીનના રૂપાંતર કર, વિશેષધારો તથા અન્ય વેરાની થતી રકમ, સરકારશ્રીમાં જમા કરાવવા અત્રેથી અરજદારશ્રીને જણાવતાં તેઓશ્રીએ આ રકમ ભારતીય સ્ટેટ બેંક, ભદ્ર શાખા, અમદાવાદ ખાતે બીનખેતી ધારાની રકમ ગામે તલાટીશ્રી પાસે જમા કરાવી પહોંચો રજુ કરેલ છે જેની વિગત એપેન્ડીક્સ-બીમાં જણાવેલ છે.

એપેન્ડીક્સ - એ (જમીનની વિગત)

ઠરાવેલ વિશેષ ધારો :
Rs. 8353/-

મોજે : ગોતા

તાલુકો :

ઘાટલોડીયા

ક્ષેત્રફળ :

26102.00 Sq.Mts.

સર્વે નંબર : 454+455+456

ટી.પી.

56

ફા.પ્લોટ નં.

188

સ.પ્લોટ નં.

બીનખેતી હેતુ :

રહેણાંક

20882.00 Sq.Mts.

વાણિજ્ય

5220.00 Sq.Mts.

એપેન્ડીક્સ - બી (વસુલ આવેલ કરવેરાની વિગત)

(૧) રૂપાંતર કરની રકમ : Rs.	365420/-	ચલણ નંબર :-	496/16	તારીખ :-	20/04/2016
(૨) વિશેષ ધારો : Rs.	8353/-	પહોંચ નંબર :-	69	તારીખ :-	21/04/2016
(૩) લોકલ ફંડ : Rs.	4177/-	પહોંચ નંબર :-	89	તારીખ :-	21/04/2016
(૪) શિક્ષણ ઉપકર : Rs.	2089/-	પહોંચ નંબર :-	08	તારીખ :-	21/04/2016

એપેન્ડીક્સ - એ માં જણાવ્યા મુજબ રૂપાંતર કર તથા અન્ય વેરાઓની રકમ કબજેદારે એપેન્ડીક્સ - બી માં જણાવેલ વિગતે જમા કરાવી, અત્રે ચલન, પહોંચો રજુ કરેલ છે. જેથી કબજેદારની માંગણી મુજબની હકીકતે, સદર જમીન અંગે અરજદારની બીનખેતીના હેતુ માટે ઉપયોગ કરવા એપેન્ડીક્સ-(એ)માં દર્શાવેલ તેઓની માલિકીની જમીન આમુખ - (૮) અને (૧૦)માં જણાવેલ મુંબઈ જમીન મહેસુલ સંહિતા અને જમીન મહેસુલ નિયમોની જોગવાઈઓ / ઠરાવોને આધિન રહીને નીચેની વધારાની શરતોને આધિન બીનખેતી પરવાનગી આપવા હુકમ કરવામાં આવે છે.

શરતો :-

- (૧) અરજદારે પ્રતિ વર્ષ ખેતી વિશેષનો ધારો (બીનખેતી દર) રહેણાંકના હેતુ માટે દર ચો.મી.ના ૦.૨૫ પૈસા પ્રમાણે રૂ.૫૨૨૧/- તથા વાણિજ્યના હેતુ માટે દર ચો.મી.ના ૦.૬૦ પૈસા પ્રમાણે રૂ.૩૧૩૨/- મળી કુલ રૂ. ૮૩૫૩/- નિયમ પ્રમાણે લોકલ ફંડ તથા શિક્ષણ શેષ ભરવો પડશે જે અંગેનો દર વખતો - વખત ફેરફારને પાત્ર રહેશે.
- (૨) અરજદારે બીનખેતીના પ્લોટની માપણી પોતાના ખર્ચે માસ - ત્રણ માં કરાવવી પડશે. માપણી થયેથી આ એન.એ. પ્લોટનું ક્ષેત્રફળ ફેરફારને પાત્ર રહેશે અને ત્યારબાદ સનદ આપવાની રહેશે તથા ડી.આઈ.એલ.આર.શ્રીએ માપણી મુજબ રેકર્ડ દુરસ્તીની નોંધ કરી સક્ષમ અધિકારીને જાણ કરવાની રહેશે.
- (૩) બાંધકામ શરૂ કરતાં પહેલાં અમદાવાદ મ્યુનિ. કોર્પો. / ઔડા પાસેથી બાંધકામ અંગેના વિગતવાર પ્લાન મંજૂર કરાવી બાંધકામની રજાચિટ્ટી મેળવવાની રહેશે. અને તે પ્રમાણે બાંધકામ કર્યા પછી થયેલ બાંધકામ અંગે અમદાવાદ મ્યુનિ. કોર્પોરેશન / ઔડા પાસેથી “બિલ્ડીંગ વપરાશ પ્રમાણપત્ર” મેળવ્યા પછી જ ઉપયોગ કરી શકાશે.
- (૪) આ બીનખેતી હુકમથી આ જમીનમાં એફ.એસ.આઈ. અંગેની કોઈ પરવાનગી આપવામાં આવતી નથી. એફ.એસ.આઈ. અંગે અરજદારે અમદાવાદ મ્યુનિ. કોર્પોરેશન / ઔડા પાસેથી જરૂરી પરવાનગી મેળવવાની રહેશે.
- (૫) શહેરી વિસ્તાર જ્યાં ટાઉન પ્લાનીંગ સ્કીમ મંજૂર થઈ ગઈ છે ત્યાં જી.ડી.સી.આર. અને ઝોનીંગના નિયમો અનુસાર બાંધકામ કરવાનું રહેશે.
- (૬) બાંધકામ બિલ્ડીંગ રેગ્યુલેશન અને રીબન ડેવલપમેન્ટ રૂલ્સથી ઠરાવેલ ધોરણોને પાત્ર રહી કરવાનું રહેશે. આ જમીનની બાજુમાં જો કોઈ રોડ - રસ્તો પસાર થતો હશે તો જે તે રસ્તાના પ્રકાર ધ્યાને લઈ રસ્તાના મધ્યેથી બાંધકામ વચ્ચે નિયમોનુસાર અંતર જાળવવાનું રહેશે. અન્યથા અરજદારની જવાબદારી થશે. આ જમીનની બાજુમાંથી પસાર થતાં ટી.પી. / ડી.પી. રોડથી નિયત અંતર છોડીને બાંધકામ કરવાનું રહેશે.
- (૭) આ જમીનનો ઉપયોગ પરવાનગી આપેલ બીનખેતીના હેતુના કામે જ કરવાનો રહેશે. અન્ય ઉપયોગ કરી શકાશે નહીં.
- (૮) અરજદારે હુકમની તારીખથી છ માસમાં બાંધકામ શરૂ કરી ત્રણ વર્ષમાં સંપૂર્ણ બાંધકામ પુરું કરવું પડશે. આ અંગે અરજદારે ખેતી સિવાયનો ઉપયોગ શરૂ કર્યેથી એક માસમાં કલેક્ટરશ્રી તથા મામલતદારશ્રીને તલાટી મારફત લેખિત ખબર આપવી પડશે તથા બાંધકામ પૂર્ણ થયે માસ એકમાં કલેક્ટરશ્રીને જાણ કરવાની રહેશે.
- (૯) બીનખેતી માટે પરવાનગી આપેલ જમીનમાં કલેક્ટરશ્રીની અગાઉથી પરવાનગી મેળવ્યા સિવાય પરવાનગી આપેલ હેતુ સિવાયનું તથા મંજૂર કરેલ બાંધકામ વિસ્તાર સિવાયની જમીન ઉપર કોઈપણ બાંધકામ કરવાનું રહેશે નહીં. પ્લાન મંજૂર કરાવી તેમાં દર્શાવેલ બાંધકામ વિસ્તાર સિવાયની માર્જન, કોમન પ્લોટ, પાર્કિંગ, રસ્તાની જગ્યા આકાશ તરફ ખુલ્લી રાખવાની રહેશે અને તેમાં કોઈપણ પ્રકારનું બાંધકામ કરવાનું રહેશે નહીં.
- (૧૦) આ જમીનમાંથી પસાર થતી ૬૬ કે.વી. તથા ૧૧ કે.વી. વીજલાઈનથી બાંધકામનું સમક્ષિતિજ અંતર ઓછામાં ઓછું અનુક્રમે ૯ મીટર તથા ૩ મીટર જાળવવાનું રહેશે.
- (૧૧) આ જમીનમાંથી ઉપરથી પસાર થતી વીજલાઈનની નીચે કોઈપણ પ્રકારનું બાંધકામ જેમ કે દુકાન, કોટ કે બાઉન્ડ્રી કરી શકાશે નહીં. તેમજ એન્ટેનાનો કેબલ કે ટીવીનો વાયર (કેબલ) પસાર કરી શકાશે નહીં.
- (૧૨) આ જમીનમાંથી પસાર થતી વીજલાઈનના સગારકામ માટે વિદ્યુત કંપનીના અધિકૃત માણસો, વાહનો કોઈપણ સમયે પસાર થઈ શકશે. અને તેમ કરતાં ભવિષ્યમાં પણ કોઈ રોકટોક કરવામાં આવશે નહીં.
- (૧૩) સવાલવાળી જમીનમાંથી ઈલેક્ટ્રીક લાઈન કે ટેલિફોન લાઈન પસાર થતી હશે તો, આવી લાઈન કે તેના થાંભલા ભવિષ્યમાં નાંખવાના થશે તો તે અંગે કોઈ વળતર મેળવવા હક્કદાવો થઈ શકશે નહીં.

- (૧૪) આ જમીનમાંથી ઉપરથી પસાર થતી વીજલાઈનથી બાંધકામ નિયમ મુજબનું, પુરતુ અંતર રાખીને કરેલ નહી હોય . તો આ બાંધકામ તોડવાનો પાત્ર ગણાશે અને તોડી નાખવાનું રહેશે.
- (૧૫) બાંધકામમાં ઝડપી સળગી ઉઠે તેવા સ્કોટક પદાર્થો વાપરી શકાશે નહી.
- (૧૬) આ જમીનમાં આવવા - જવાના રસ્તા અંગે કે વરસાદના પાણીનો નિકાલ બાબતે જો કોઈ પ્રશ્ન ઉપસ્થિત થશે તો તે અંગેના નિકાલની વ્યવસ્થા કરવાની જવાબદારી અરજદાર - ખાતેદારની રહેશે. ચોમાસાનું પાણી ભરાઈ ન રહે તેવું પુરાણ કરી રોડ લેવલ કરતાં પ્લીથ ઉંચી લેવાની રહેશે.
- (૧૭) આ જમીનમાં વરસાદી પાણીના ભુગર્ભ વહન એટલે કે સંચય માટે દર મકાન / બહુમાળી મકાન દીઠ એકનો દર આ જમીનમાં પરકોલેટીંગ બોરની વ્યવસ્થા અચૂક કરવાની રહેશે. તથા વરસાદી પાણીના નિકાલની વ્યવસ્થા કરીને બાંધકામ કરવાનું રહેશે.
- (૧૮) પ્લોટમાં બાંધકામ સિવાયનો ખુલ્લો ભાગ આકાશ તરફ ખુલ્લો રાખવાનો રહેશે. આ જમીનની નજીકમાં પસાર થતા રોડ / રસ્તા અંગે, રસ્તાની બાજુએ કંપાઉન્ડ વોલની ઉંચાઈ ૧.૦૫ મી. થી વધારે કરી શકાશે નહી.
- (૧૯) મંજૂર થયેલ નકશા મુજબ આરોગ્ય અને સ્વાસ્થ્યની દ્રષ્ટિએ ગંદા પાણીના નિકાલની જોગવાઈ કરવાની રહેશે.
- (૨૦) આ જમીનમાં કે નજીકમાં આવેલ કોઈ જમીનમાં ઓ. એન. જી. સી. ના તેલકુવા તેમજ તેલ / ગેસ પાઈપલાઈન આવેલ હોવાના કિસ્સામાં તેવા કુવા / પાઈપલાઈનની નિયમોનુસાર જાળવવાપાત્ર અંતર છોડીને બાંધકામ કરવાનું રહેશે.
- (૨૧) નર્મદા કેનાલ / અન્ય સિંચાઈ કેનાલની નજીકમાં આવેલ જમીનની બાબતમાં અરજદારે સૂચિત બાંધકામ માટે જાળવવાના થતાં અંતર અંગેના નિયમોનું પાલન કરવાનું રહેશે.
- (૨૨) અરજદારે / જ્યાં જરૂરી હોય ત્યાં કેન્દ્ર સરકાર કે રાજ્ય સરકારના કાયદા નીચે રક્ષિત સ્મારક (Protected Monuments) તરીકે જાહેર કરેલ પ્રાચીન સ્મારકથી ૧૦૦ મીટર સુધીનું અંતર જાળવવાની પ્રવર્તમાન જોગવાઈઓનું પાલન કરવાનું રહેશે.
- (૨૩) આ પરવાનગી સ્થાનિક સત્તા મંડળ દ્વારા મંજૂર કરવામાં આવતા નકશા તેમજ વિકાસ પરવાનગીની શરતોના અમલીકરણને આધિન રહેશે. વધુમાં વિકાસ પરવાનગી અન્વયે કરવામાં આવતો વિકાસ અને તેનો વપરાશ વિકાસ યોજનાના નિયંત્રણ / વિનિમયો તેમજ ઔડા / મ્યુનિ. કોર્પોરેશન અને રાજ્ય સરકાર દ્વારા આપવામાં આવતાં વખતો વખતના આદેશ / નિર્દેશનોને આધિન રહેશે. જમીનના માલિક / કબજેદારોએ પરવાનગી હેઠળની જમીનનો વિકાસ સંબંધિત સત્તા મંડળની વિકાસ પરવાનગીને આધિન રહીને જ કરવાનો રહેશે.
- (૨૪) આ પરવાનગીથી ગણોત્ત ધારા, શીલીંગ ધારા, શહેરી જમીન ટોચ મર્યાદા ધારા તેમજ અન્ય કાયદાઓની જોગવાઈઓને બાધ રહેશે નહી. એટલે કે અન્ય કાયદા નિયમોની જોગવાઈઓ અન્વયે જો કોઈ કાર્યવાહી કરવાની થતી હશે તો તે અંગે નિયમોનુસારની કાર્યવાહી કરી શકાશે.
- (૨૫) ઔદ્યોગિક હેતુ માટે મંજૂરી માંગેલ હોય તો બાંધકામ કરતાં પહેલા જિલ્લા ઉદ્યોગ અધિકારીની જરૂરી મંજૂરી મેળવ્યા બાદ જ આગળની કાર્યવાહી કરવાની રહેશે.
- (૨૬) ફ્લોર મીલ, સિનેમા / ટુરીંગ સિનેમા / થિયેટર માટે બીનખેતી પરવાનગીના કામે જિલ્લા મેજિસ્ટ્રેટની જરૂરી મંજૂરી મેળવી આગળની કાર્યવાહી કરવાની રહેશે.
- (૨૭) પેટ્રોલ, ડીઝલ, કેરોસીન, સી. એન. જી., એલ. પી. જી., પંપ નાખવા માટે બીનખેતી પરવાનગીના કામે બાંધકામ શરૂ કરતાં પહેલા જિલ્લા મેજિસ્ટ્રેટની જરૂરી મંજૂરી મેળવી આગળની કાર્યવાહી કરવાની રહેશે.
- (૨૮) સવાલવાળી જમીન જો જેલથી નજીક હોય તો ૧૮૪ મીટરનું અંતર છોડી બાંધકામ કરવાનું રહેશે.

- (૨૯) સવાલવાળી જમીન જો રેલ્વે હદની નજીક હોય તો રેલ્વેની હદથી ૩૦ મીટર જગ્યા છોડી બાંધકામ કરવાનું રહેશે.
- (૩૦) બીનખેતી માંગવામાં આવી હોય તેવી જમીન જો એરોડ્રામ આસપાસના ૨૦ કિ.મી.ના ત્રિજ્યામાં આવતી હોય ત્યારે બાંધકામની ઉંચાઈ તથા એરોડ્રામની દ્રષ્ટિએ જરૂરી એવું ના વાંધા પ્રમાણપત્ર સિવિલ એવીએશન ખાતા પાસેથી મેળવવાનું રહેશે અને સીવીલ એવીએશન ખાતાના નિયમોનું પાલન કરવાનું રહેશે.
- (૩૧) ભારતીય વાયુસેનાના હવાઈ મથક તથા ઈન્સ્ટોલેશનથી ૮૦૦ મીટરની ત્રિજ્યા બહાર બાંધકામ કરવાનું રહેશે.
- (૩૨) અરજદારે/જ્યાં જરૂરી હોય ત્યાં ભારતીય વન અધિનિયમ હેઠળ અનામત વન જમીન કે રક્ષિત વન તરીકે જાહેર કરેલ વન/જમીનથી જાળવવાના થતાં અંતર બાબતની જોગવાઈઓનું પાલન કરવાનું રહેશે.
- (૩૩) અરજદારે/જ્યાં જરૂરી હોય તેવાં વન્યજીવન સંરક્ષણ અધિનિયમ - ૧૯૭૨ અન્વયે અભ્યારણ અથવા રાષ્ટ્રીય ઉપવન તરીકે જાહેર કરેલ કોઈપણ વિસ્તારની હદથી જાળવવાના થતાં અંતર બાબતની જોગવાઈઓનું પાલન કરવાનું રહેશે.
- (૩૪) આ હુકમમાં અગર સનદમાં કોઈ કારકુની અથવા ગણતરીની ભુલ હશે તો તેમાં સુધારો થઈ શકશે.
- (૩૫) આ પરવાનગી અરજદારે રજુ કરેલ વિગતોને આધારે આપવામાં આવેલ છે. રજુ થયેલ કોઈ વિગત ખોટી હોવાનું જાહેર થયેથી કે ઉપરની કોઈપણ શરતોનો ભંગ થયેથી આ પરવાનગી આપોઆપ રદ થયેલી ગણાશે તથા જમીન મહેસુલ કાયદા કલમ - ૬૫ના ભંગ બદલ કાયદાની જોગવાઈ હેઠળ પગલાં લેવાને પાત્ર રહેશે. અને તત્કાલિન અમલમાં હોય તેવા બીજા કોઈપણ કાયદાની જોગવાઈઓના બાધ વિના ઈન્ડિયન પીનલ કોડ હેઠળ કબજેદારો ફોજદારી ગુન્હા માટે શિક્ષાત્મક પગલા લેવાને પાત્ર બનશે. તથા જમીન મહેસુલ કાયદાની કલમ - ૬૬ તથા નિયમોના નિયમ - ૧૦૦ અનુસાર યોગ્ય તે દંડાત્મક કાર્યવાહી કરવામાં આવશે અને બાંધકામ દુર કરાવવા સહિતના એક કે વધુ પગલાં લેવામાં આવશે.
- (૩૬) જો ટી.પી. ફાઈનલ થઈ કોઈ કપાત કરવાની થશે તો તેને આધિન પ્લાન મંજૂરી કરનાર અધિકારીશ્રીએ મંજૂરી આપવાની રહેશે.

રવાના કરવા પ્રમાણિત

વધારાના ચીટનીશ ટુ કલેક્ટર, અમદાવાદ

પ્રતિ,
શ્રી બાલુજી પુંજાજી વિગેરે
રહે. એ-૬, માર્તિનંદન વિહાર,
આરોહીવીલાના ગેટમાં, બસેરા પાર્ટી પ્લોટ સામે,
રીંગ રોડ, બોપલ, અમદાવાદ.



સહી/-

(આર.કે.બેનીવાલ)

જિલ્લા કલેક્ટર, અમદાવાદ

નકલ રવાના :-

- (૧) મામલતદારશ્રી ઘાટલોડીયા તરફ.
૨/- આગળની જરૂરી કાર્યવાહી તથા સનદ ભરાવવા અંગે ઘટતી કાર્યવાહી હાથ ધરવા સારું.
- (૨) તલાટીશ્રી ગોતા તરફ આગળની કાર્યવાહી તથા ગા.ન.નં. ૨માં જરૂરી નોંધ કરવા સારું.
- (૩) ડીસ્ટ્રીક્ટ ઈન્સ્પેક્ટરશ્રી, લેન્ડ રેકૉર્ડ્સ, મોજણી ભવન, ભીમજીપુરા, નવા વાડજ, અમદાવાદ તરફ સારું.
- (૪) મ્યુનિ. કમિશનરશ્રી (એસ્ટેટ) દાણાપીઠ, અમદાવાદ/મુખ્ય કારોબારી અધિકારીશ્રી, ઔડા, ઉસ્માનપુરા, અમદાવાદ તરફ સારું.
- (૫) નાયબ કલેક્ટરશ્રી, બીનખેતી શાખા, કલેક્ટર કચેરી, અમદાવાદ તરફ જાણ સારું.
- (૬) સિલેક્ટ ફાઈલે.
- (૭) ઈ-ધરા કેન્દ્ર તરફ.
- (૮) EWMS ટેબલે (EWMS નં. ૨૪૭૬૭)



भारतीय विमानपत्तन प्राधिकरण AIRPORTS AUTHORITY OF INDIA

(1) Chandrakantbhai Gangarambhai Patel, (2) Dilipbhai Dahyabhai Patel

Date: 29-11-2019

401, 402, Ratnam Tower,
Judges Bungalows, Bodakdev,
Ahmedabad - 380054. Mbl.

System Generated Auto Assessment for Height Clearance

1. Airports Authority of India (AAI) in pursuance of responsibility conferred by and as per the provisions of Govt. of India (Ministry of Civil Aviation) order GSR 751 (E) dated 30th Sep. 2015 for Safe and Regular Aircraft Operations has assessed the site data filled by the applicant.

2. Assessment details for Height Clearance:

NOC ID :	AHME/WEST/B/112119/434567
Applicant Name*	Jagdish B Patel
Site Address*	T. P. S. No. 56 (Sola – Gota - Ognaj), F. P. No. 188/1, 188/2, Survey No. 454 PLUSE 455 PLUSE 456/1, At Gota Taluka Ghatlodiya District Ahmedabad
Site Coordinates*	23 06 08.86N 72 31 24.88E, 23 06 07.70N 72 31 26.70E, 23 06 11.40N 72 31 27.20E, 23 06 10.40N 72 31 28.90E
Site Elevation in mtrs AMSL as submitted by Applicant*	55.06 M
Type Of Structure*	Building

*As provided by applicant

Your site is located at a distance 11097 mts from ARP and lies in the grid I7 of the published CCZM of Ahmedabad airport. The Permitted top elevation for this grid is 135 mts.

Since the requested top elevation 125.06 mts in AMSL is below CCZM permitted top elevation, the NOC for height clearance is not required from Airports Authority of India.

3. This assessment is subject to the terms and conditions as given below:

a. The site-elevation and site coordinates provided by the applicant are taken for calculation of the permissible top elevation for the proposed structure. If however, at any stage it is established that the actual data is different from the one provided by the applicant, this assessment will become invalid.

b. The Site coordinates as provided by the applicant in the NOC application has been plotted on the street view map and satellite map as shown in ANNEXURE. Applicant/Owner to ensure that the plotted coordinates corresponds to his/her site. In case of any discrepancy, this assessment shall be treated as null and void

c. Airport operator or his designated representative may visit the site (with prior coordination with applicant or owner) to ensure that assessment terms & conditions are complied with.

d. The assessment is further subject to the provisions of Section 9-A of the Indian Aircraft Act, 1934 and any notifications issued there under from time to time including the Aircraft (Demolition of Obstruction caused by Buildings and Trees etc.) Rules, 1994.



भारतीय विमानपत्तन प्राधिकरण
AIRPORTS AUTHORITY OF INDIA

e. The applicant is responsible to obtain all other statutory clearances from the concerned authorities including the approval of building plans. This assessment for height is to ensure the safe and regular aircraft operations and shall not be used as document for any other purpose/claim whatsoever, including ownership of land etc.

f. Use of oil, electric or any other fuel which does not create smoke hazard for flight operations is obligatory, within 8 KM of the Aerodrome Reference Point.

g. This assessment has been issued w.r.t. the Civil Airports as notified in GSR 751(E). Applicant needs to seek separate NOC for Defence, if the site lies within jurisdiction of Defence Airport. Applicants also need to seek clearance from state Govt. as applicable, for sites which lies in the jurisdiction of unlicensed civil aerodrome as outlined in Rule 13 of GSR751 (E).

This assessment is system auto generated and thus does not require any signature

Designated Officer

Region Name: WEST

Address: General Manager (ATM)

Email ID: vaah.noc@aai.aero

Contact No: 079-22858111

S. M. SAIYAD, IFS
MEMBER SECRETARY
SEIAA (GUJARAT)



Government of Gujarat

STATE LEVEL ENVIRONMENT
IMPACT ASSESSMENT
AUTHORITY
GUJARAT

No. SEIAA/GUJ/EC/8(a)/ 403 /2020

Date: 5 JUN 2020

BY R.P.A.D
Time Limit

Sub: Environment Clearance for the Building Construction Project at Survey Number: 454+455+456, F.P. Number: 188/2, T.P. Number: 56, Gota, Ahmedabad proposed by Mr. Chandrakant G. Patel & Mr. Dilipbhai D. Patel. Construction project in Category 8 (a) of Schedule annexed with EIA Notification dated 14/09/2006.

Ref: Your Proposal No. SIA/GJ/MIS/137631/2020.

Dear Sir,

This has reference to your application along with Form-I, Form-1 A dated 07/02/2020, seeking Environmental Clearance under Environment Impact Assessment Notification, 2006. The project was scheduled for hearing in the SEAC meeting held on 24/02/2020.

The proposal is for Environmental Clearance for the Building Construction Project at Survey Number: 454+455+456, F.P. Number: 188/2, T.P. Number: 56, Gota, Ahmedabad proposed by Mr. Chandrakant G. Patel & Mr. Dilipbhai D. Patel. This is a proposed building construction project having plot area of 7,275.0 m² and the proposed FSI area of the project is 19,640.53 m² with proposed built up area of 37,619.45 m². As the built up area is >20,000 m² and <1,50,000 m², it falls in the category 8(a) of the Schedule of EIA Notification, 2006.

The project will comprise of 03 numbers of buildings. No. of Blocks: 05. Scope of buildings/blocks are: 2 level Basement + Ground floor + 13 floors and No.& size of Residential Units are: 230 flats and No.& size of Commercial Units are: 42 shops.

The project activity is covered in 8(a) and falls in Category 'B'. Since the proposed project is in item no.8 of the EIA notification, 2006, it does not need Public Consultation as per Para 7(i) III. Stage (3) (d) – Public Consultation of EIA Notification, 2006.

The SEAC, Gujarat had recommended the project vide their letter dated 06/03/2020 to grant Environmental Clearance to the SEIAA, Gujarat based on the decision taken during SEAC meeting held on 24/02/2020. The proposal was considered by SEIAA, Gujarat in its meeting held on 13/03/2020 at Gandhinagar. After careful consideration, the SEIAA hereby accords Environmental Clearance to above project under the provisions of EIA Notification dated 14th September, 2006 subject to the compliance of the following conditions.

A. PROJECT SPECIFIC CONDITIONS:

1. Necessary prior permission shall be obtained from the concerned competent Authority of cutting the trees existing within the premises and the conditions stipulated therein shall be fulfilled in true spirit.

A.1 CONSTRUCTION PHASE:

A.1.1 WATER:

2. Fresh water requirement during the construction phase shall be 17.5 KL/day and it shall be met through local water tankers. No ground water shall be tapped during the construction phase.
3. Sewage generated during the construction phase shall be disposed off through septic tank & soak pit.

A.2 OPERATION PHASE:

A.2.1 WATER

4. Total water requirement during the operation phase shall be 168.36 KL/day, out of which fresh requirement of 112.35 KL/day shall be met through water supply system of Ahmedabad Municipal Corporation (AMC) and the remaining 56.01 KL/day of water requirement shall be met through treated sewage. No ground water shall be tapped during the operation phase. Metering of the water shall be done and its records shall be maintained.
5. Sewage generation during operation phase shall be 132.02 KL/day which shall be treated in the proposed onsite Sewage Treatment Plant.

The unit shall install and efficiently operate STP of adequate capacity for treating the sewage to be generated during operation phase to achieve the GPCB norms at the STP outlet. Treated sewage conforming to GPCB



norms shall be utilized within premises for gardening & flushing purpose at the maximum extent possible. Only remaining quantity of treated sewage shall be disposed off through drainage line of Ahmedabad Municipal Corporation (AMC).

7. A proper logbook of STP operation and also showing the quantity of treated sewage utilization within premises & quantity of treated sewage discharged into the drainage line shall be maintained and furnished to the GPCB from time to time.
8. Dual plumbing system with separate tanks and lines shall be provided for utilization of treated sewage for flushing.
9. No bore well shall be constructed and existing bore well/s, if any, shall be either sealed or converted into the recharge well.
10. Rain water harvesting from rooftop and paved areas and ground water recharge through 2 nos. of percolation wells shall be carried out as per the details submitted. Before recharging the run off, pre-treatment must be done to remove suspended matter.

A.2.2 AIR:

11. A D. G. set (1 x 40 KVA) proposed as backup power shall be of enclosed type and confirm to prescribe standards under EPA rules. Necessary acoustic enclosures shall be provided at diesel generator set to mitigate the impact of noise.
12. The exhaust of the D. G. Set shall be at least 3 m above roof top.
13. The gaseous emissions from the D.G. Sets shall conform to the standards prescribed under EPA rules as amended from time to time. At no time, the emission levels shall go beyond the stipulated standards.

A 2.3 SOLID WASTE:

14. The solid waste generated shall be properly collected and segregated at source. The biodegradable waste shall be converted into useful end product by treating it into the proposed onsite Organic Waste Converter and the recyclable waste shall be sold to vendors whereas the other garbage shall be disposed off properly as per the provisions made by the Ahmedabad Municipal Corporation (AMC).

A 2.4 SAFETY :

15. Fire fighting facilities like fire extinguishers, hose reel, wet riser, manually operated electric fire alarm system, automatic sprinkler system in basement & HP, underground static water storage tank-150 KL capacity, terrace tank -50 KL capacity (total capacity), pump near underground static water storage tank (fire pump) with minimum Pressure of 3.5 kg/cm² at terrace level –one electric and one diesel pump of capacity 2 280 lit/min and one electric pump of capacity 180 lit/min etc. shall be provided as proposed.
16. All the staircases and lifts shall open out at ground level from the highest point of building [with access from each floor] for emergency evacuation. Two staircases shall be provided in each building having floor area more than 500 m² on each floor.
17. In basement at least two separate ramps of adequate width and slope shall be provided, located preferably at opposite ends.
18. Provision for adequate air changes per hour in the basement shall be made so as to avoid build up of CO in the area.
19. Car park exhaust system equipped with CO (Carbon Monoxide) sensor shall be provided to ensure operation of exhaust fans as CO concentration levels.
20. Clear peripheral margin space of atleast 6 m, excluding the width for tree plantation, shall be provided for unobstructed & easy movement of vehicles in case of emergency.

A2.5 PARKING / TRAFFIC CONGESTION:

21. Minimum parking space of 13,062.2 m² [11,160.76 m² in basement + 1,451.44 m² in hollow plinth + 450 m² as open surface parking] shall be provided as proposed.

A 2.6 ENERGY CONSERVATION:

22. Energy conservation measures viz. maximum use of natural lighting through architectural design, energy efficient motors & pumps, water efficient taps, solar lights in open & landscape areas – 20 solar street lights, 60 KW solar panel, use of aerated blocks & RMC, use of LED lighting fixtures and low voltage lighting, roof-top thermal insulation, rain water harvesting & ground water recharge through 2 nos. of percolating wells etc. shall be implemented as proposed.

A 2.7 GREEN BELT :

23. Green belt area of 742.52 m² comprising of 350.0 m² tree covered area with 182 trees within premises shall be developed as proposed. The other open spaces inside the plot shall be suitably landscaped and covered with vegetation of indigenous tree species.

B. GENERAL CONDITIONS :

B1. PRE -CONSTRUCTION AND CONSTRUCTION PHASE:

24. Roads leading to or at construction site must be paved and blacktopped (i.e. – metallic roads).
25. No excavation of soil shall be carried out without adequate dust mitigation measures in place.
26. Grinding and cutting of building materials in open area shall be prohibited.
27. Construction material and waste should be stored only within earmarked area and road side storage of construction material and waste shall be prohibited.
28. Construction and demolition waste processing and disposal site shall be identified and required dust mitigation measures be notified at the site.
29. Dust mitigation measure shall be displayed prominently at the construction site for easy public viewing.
30. Environment Management Cell shall be formed, which shall supervise and monitor the environment related aspects of the project during construction and operational phases in addition to observance of Gujarat Building and other Construction Workers'(Regulation of Employment & Conditions of Service) Rules 2003.
31. Prior permission from the competent authority shall be obtained for cutting of the existing trees before site preparation work is commenced.
32. Water demand during construction shall be reduced by use of curing agents, super plasticizers and other best construction practices.
33. Wind – breaker of appropriate height i.e. 1/3rd of the building height and maximum up to 10 meters shall be provided. Individual building within the project site shall also be provided with barricades.
34. Regular water sprinkling shall be done in vulnerable areas for controlling fugitive emission.
35. No uncovered vehicles carrying construction material and waste shall be permitted.
36. No loose soil or sand or construction & demolition waste or any other construction material that cause dust shall be left uncovered. Uniform piling and proper storage of sand to avoid fugitive emissions shall be ensured.
37. Structural design of the project shall strictly adhere to the seismic zone norms for earthquake resistant structures.
38. The planning, designs and construction of all buildings shall be such as to ensure safety from fire.
39. The project proponent shall ensure maximum employment to the local people.
40. All required sanitary and hygienic measures shall be provided before starting the construction activities and to be maintained throughout the construction phase.
41. Provision shall be made for housing of construction labor within the site with all necessary infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical healthcare, crèches, electricity & ventilation, canteen, rest rooms, safe disposal system for garbage, first aid, medical and emergency facilities etc. to ensure that they do no ruin the existing environmental condition. The housing may be in the form of temporary structures to be removed after completion of the project.
42. Adequate personal protective equipments shall be provided to the construction workers to ensure their safety and the project proponent shall ensure its usage by the labours.
43. First Aid Box shall be made readily available in adequate quantity at all the times.
44. Training shall be given to all workers on construction safety aspects.
45. The project proponent shall strictly comply with the Building and other Construction Workers'(Regulation of Employment & Conditions of Service) Act 1996 and Gujarat rules made there under and their subsequent amendments.
46. The overall noise level in and around the project area shall be kept well within the prescribed standards by providing noise control measures including acoustic insulation, hoods, silencers, enclosures vibration dampers etc. on all sources of noise generation.
47. Ambient noise levels shall conform to residential standards both during day and night. Incremental pollution load on the ambient air and noise quality shall be closely monitored during construction phase
48. The noise generating equipments, machinery and vehicles shall not be operated during the night hours and shall be maintained properly to avoid generation of high noise due to wear and tear.



49. Use of diesel generator sets during construction phase shall be strictly with acoustic enclosure and shall conform to the EPA Rules for air and noise emission standards.
50. Safe disposal of wastewater and municipal solid wastes generated during the construction phase shall be ensured.
51. All topsoil excavated during construction activity shall be used in horticultural / landscape development within the project site.
52. Construction materials and debris shall be properly stored and handled to avoid negative impacts such as air pollution and public nuisances by blocking the roads and public passages.
53. Construction debris shall be reused in construction of roads, levelling the site etc. Waste packaging material (like used cement bags, waste paper, cardboard packing material), metal scraps etc. shall be sold to recyclers or shall be sent to the nearest municipal solid waste landfill site.
54. Excavated earth to be generated during the construction phase shall be utilized within the premises to the maximum extent possible and balance quantity of excavated earth shall be disposed off with the approval of the competent authority after taking the necessary precautions for general safety and health aspects. Disposal of the excavated earth during construction phase shall not create adverse effect on neighbouring communities.
55. Provisions of Construction & Demolition Waste Management Rules-2016 shall be strictly adhered to.
56. Vehicles hired for bringing construction material at the site shall be in good conditions and conform to applicable air and noise emission standards and shall be operated only during day time and non-peak hours.
57. Project proponent shall ensure use of eco-friendly building materials including fly ash bricks, fly ash paver blocks, Ready Mix Concrete [RMC] and lead free paints in the project.
58. Fly ash shall be used in construction wherever applicable as per provisions of Fly Ash Notification under the E.P. Act, 1986 and its subsequent amendments from time to time.
59. Use of glass shall be minimal and only low emissive glass shall be used in the project to reduce the electricity consumption and load on air conditioning.


B2. OPERATION PHASE AND LIFE TIME:

60. Low water consuming devices shall be provided. Fixtures for showers, toilet, flushing and drinking shall be of low flow either by use of aerators/ diffusers or pressure reducing devices etc.
61. A water meter shall be installed on rain water harvesting & ground water recharge well system & compliance report of the same shall be submitted to concerned authorities.
62. Used oil shall be sold only to the registered recycler.
63. Provisions of Solid Waste Management Rules-2016 shall be strictly adhered to.
64. Requisite fire fighting facilities as per the requirement of NBC and Gujarat Fire Prevention and Life Safety Measures Act-2013 along with the rules & regulations made there under shall be provided.
65. Underground fire water storage tanks and terrace water storage tanks of adequate capacity shall be provided as proposed. Adequate provision shall be made to ensure that water from the Fire Water Tank shall not be used for any other purpose.
66. Dedicated power back up system shall be provided in the case of power failure & emergency of fire water pumps.
67. First Aid Box shall be made readily available in adequate quantity at all the times.
68. Main entry and exit shall be separate and clearly marked in the facility
69. Necessary emergency lighting system along with emergency power back up system shall be provided. Further, necessary auto glow signage at all appropriate places shall be provided to guide the people towards exits and assembly points during emergency.
70. Sufficient peripheral open passage shall be kept in the margin area for free movement of fire tender/ emergency vehicle around the premises.
71. The overall noise level in and around the project area shall be kept well within the prescribed standards by providing noise control measures including acoustic insulation, hoods, silencers, enclosures vibrations dampers etc. on all sources of noise generation including D.G.Sets. The ambient noise levels shall conform to the standards prescribed under the Environment (Protection) Act and Rules.
72. The area earmarked for the parking shall be used for parking only. No other activity shall be permitted in this area.
73. Traffic congestion near the entry and exit points from the roads adjoining the proposed project site shall be avoided. No public space including the service road shall be used or blocked for the parking.

74. The project proponent shall install energy efficient devices, appliances, motors, and pumps conforming to the Bureau of Energy Efficiency norms.
75. The transformers and motors shall have minimum efficiency of 85%.
76. Only variable frequency motor drives shall be used in project.
77. Application of solar energy shall be incorporated for illumination of common areas, lighting for gardens and street lighting. In addition the provision for solar water heating system shall also be provided.
78. Use of glass shall be minimal to reduce the heat island effect as well as to reduce the electricity consumption.
79. The area earmarked as green area shall be used only for plantation and shall not be altered for any other purpose.
80. Drip irrigation/low volume, low angle sprinkler system shall be used for the lawns and other green area including tree plantation.
81. The project proponent shall inform to SEAC / SEIAA regarding the transfer of management responsibility to the Society / Association to be formed for the proposed project with all the supporting documents. The Society / Association formed for further management of the proposed project shall be responsible for compliance of all the conditions stipulated in the Environmental Clearance order.
82. Environmental Clearance granted for the project on the basis of documents related to land possession submitted shall become invalid in case the actual land for the project site turns out to be different from the land considered at the time of appraisal of the project and mentioned in the EC.
83. All other statutory clearances such as N.A. permission, approvals for storage of diesel from PESO, Fire Department, Airports Authority of India etc., if applicable, shall be obtained by the project proponent from the competent authorities.
84. All the conditions as may be stipulated in the N.A. order, Development permission, Building Use permission, NOC obtained from Fire Department etc. shall be strictly complied with.
85. The project management shall also comply with all the environment protection measures, risk mitigation measures and safeguards proposed by them.
86. All the commitments / undertakings given to the SEAC during the appraisal process for the purpose of environmental protection and management shall be strictly adhered to.
87. The project proponent shall also comply with any additional condition that may be imposed by the SEAC or the SEIAA or any other competent authority for the purpose for the environmental protection and management.
88. All the terms & conditions prescribed in the amendment of EIA Notification – 2006 published by the MoEF&CC vide its Notification No. S.O. 3999(E) dated 9th December, 2016 shall be complied with letter & spirit.
89. The project proponent shall strictly comply with the Gujarat Building and other Construction Workers' (Regulation of Employment & Conditions of Service) Rules 2003 as well as Gujarat Lifts & Escalators Rules as amended from time to time.
90. No further expansion or modifications in the project likely to cause environmental impacts shall be carried out without obtaining prior Environment Clearance from the concerned authority.
91. The above conditions shall be enforced, inter-alia under the provisions of the water (Prevention & Control of Pollution) Act, 1974, Air (Prevention & Control of Pollution) Act, 1981, the Environment (Protection) Act 1986 and the Hazardous Wastes (Management Handling and Tran boundary) Rules, 2008, Building and Other Construction Workers' (Regulation of Employment & Conditions of Service) Act-1996, The Gujarat Lifts and Escalators Act-2000 along with their amendments and rules.

B3. OTHER:

92. The project proponent shall allocate separate fund of Rs. 111 lakhs to provide medical facility for Leprosy patients, provision to upgrade infrastructure at Sahyog Krust (Leprosy) trust, organize health check-up camp for senior citizens at Civil hospital of Sola, provision of uniforms, books, periodicals & providing infrastructure facility of primary school in Gota area, provision of drinking water facility(RO plant) at 2 primary schools in Gota area etc. for the next 3 years in accordance to the MoEFCC's Office Memorandum No. F.No.22-65/2017-IA.III dated 01/05/2018. The entire activities proposed under CER shall be monitored and the monitoring report shall be submitted to the regional office of MoEFCC as a part of half-yearly compliance report and to district collector. The monitoring report shall be posted on the website of the project proponent.
93. The project authorities shall earmark adequate funds to implement the conditions stipulated by SEIAA as well as GPCB along with the implementation schedule for all the conditions stipulated herein. The funds so provided shall not be diverted for any other purpose.



94. The project proponent shall adhere to provisions made for Corporate Environment Responsibility "CER" in Office Memorandum dated 01/05/2018 by Ministry of Environment, Forests & Climate Change and its amendments from time to time in a letter and spirit.
95. The applicant shall inform the public that the project has been accorded environmental clearance by the SEIAA and that the copies of the clearance letter are available with the GPCB and may also be seen at the Website of SEIAA/ SEAC/ GPCB. This shall be advertised within seven days from the date of the clearance letter, in at least two local newspapers that are widely circulated in the region, one of which shall be in the Gujarati language and the other in English. A copy each of the same shall be forwarded to the concerned Regional Office of the Ministry.
96. It shall be mandatory for the project management to submit half-yearly compliance report in respect of the stipulated prior environmental clearance terms and conditions in hard and soft copies to the regulatory authority concerned and shall be uploaded on website of Gujarat Real Estate Regulatory Authority, on 1st June and 1st December of each calendar year.
97. The project authorities shall also adhere to the stipulations made by the Gujarat Pollution Control Board.
98. The project authorities shall inform the GPCB, Regional Office of MoEF&CC and SEIAA about the date of financial closure and final approval of the project by the concerned authorities and the date of start of the project.
99. The SEIAA may revoke or suspend the clearance, if implementation of any of the above conditions is not found satisfactory. This environmental clearance is valid for seven years from the date of issue.
100. Any appeal against this environmental clearance shall lie with the National Green Tribunal, if preferred, within a period of 30 days as prescribed under Section 16 of the National Green Tribunal Act, 2010.
101. Submission of any false or misleading information or data which is material to screening or scoping or appraisal or decision on the application makes this environment clearance cancelled.

With regards,
Yours sincerely,

(S. M. SAIYAD)
Member Secretary

Issued to:

Mr. Jaykumar Bhatt,
Aaryan Probuild LLP, 905, 906,
9th Floor, Arista Nusiness Space,
Sindhuhavan Road, Bodakdev,
Ahmedabad-380054



AHMEDABAD MUNICIPAL CORPORATION

FIRE & EMERGENCY SERVICE

DANAPITH FIRE STATION, (H. Q.)AHMEDABAD - 380 001

PH. : (079) 22148466 / 67 / 68, 32981178, 32981500 FAX : (079)

No. - OPN212908012020 Dt.:08/01/2020

To,

COMM + RESI,

401, 402,RATNAM TOWER , JUDGES BUNGLOWS, BODAKDEV AHMEDABAD

401, 402,RATNAM TOWER , JUDGES BUNGLOWS, BODAKDEV AHMEDABAD

Sub: Fire safety & protection, opinion for a proposed high-rise building / Low-Rise Building - High Rise Building

Sir,

This is to intimate that , the plans submitted for, High Rise Building , have all the required line drawings and write-up are as per the requirement of fire prevention and protection.

All norms as per the GDCR (2021) & CBD by AUDA have to be followed as far as the construction and Fire Prevention and Protection system, are to be followed.

1.5 Meters for - 18 to 25 meters building heights,

2.00 meters for 25 meters to above height, clear in width.

The staircase and lift shafts shall not go to the basement but if they go they have to be protected by 2 hours fire resistant construction including the doors.

A motorable road with 45 ton load bearing capacity and minimum as metion in table; is required around the building without obstruction to a clear motorable passage for fire/rescue vehicles.

Any transformer to be installed shall be away from the building & leaving open Space required around the building and below building height wise open space required around the building.

Margin for different types of building;

1) 8 to 25 Meters building - 3 meters

Plot area more than 750 sq. mt. : 4 Meters

2) Up to 45 Meters building : 6 Meters

3) Up to 70 Meters building : 8 Meters

The gate (entry) to the premises shall be minimum 6 meters or more if required, in width, entry gate to be provided on both sides.

The Fire Protection system shall be as mentioned in the approved plans.

1. All basements parking and HPP shall be fully sprinklered.

2. All lower basements should have positive pressure ventilation.

3. Electric Cable Shaft should have fire resistant doors.

In this Filed we can write what system they required in building – So whatever here we write that can be mention in

final opinion letters

Builder name			COMM + RESI			
Address			401, 402,RATNAM TOWER , JUDGES BUNGLOWS, BODAKDEV AHMEDABAD			
T.P.No.			56 (GOTA)			
F.P.No.			188/2			
R.S.No.			454+455+456/1			
Sub Plot No.			00			
Surrounding Margin from building						
Common Plot Margin from building						
Building Types			High Rise Building			
	A		B		C+D+E	
Fire Opinion Remarks	•ALL BASEMENTS PARKING & HPP SHALL BE FULLY SPRINKLERED. •ALL BASEMENTS SHOULD HAVE POSITIVE PRESSURE VENTILATION. •ELECTRIC CABLE DUCT SHOULD HAVE FIRE RATED DOORS AT ALL LEVEL AND TO BE KEPT OPEN FROM TERRACE AND LAST BASEMENT LEVEL. •STAIRCASE AND LIFT LOBBY TO BE ENCLOSED AT BASEMENT.		•ALL BASEMENTS PARKING & HPP SHALL BE FULLY SPRINKLERED. •ALL BASEMENTS SHOULD HAVE POSITIVE PRESSURE VENTILATION. •ELECTRIC CABLE DUCT SHOULD HAVE FIRE RATED DOORS AT ALL LEVEL AND TO BE KEPT OPEN FROM TERRACE AND LAST BASEMENT LEVEL. •STAIRCASE AND LIFT LOBBY TO BE ENCLOSED AT BASEMENT.		•ALL BASEMENTS PARKING, HPP & SHOPS AT ALL LEVEL SHALL BE FULLY SPRINKLERED. •ALL BASEMENTS SHOULD HAVE POSITIVE PRESSURE VENTILATION. •ELECTRIC CABLE DUCT SHOULD HAVE FIRE RATED DOORS AT ALL LEVEL AND TO BE KEPT OPEN FROM TERRACE AND LAST BASEMENT LEVEL. •STAIRCASE AND LIFT LOBBY TO BE ENCLOSED AT BASEMENT.	
Block Height From Ground Level to Top Slab(In Meter)	45		45		45	
	Use	Height(In Meter)	Use	Height(In Meter)	Use	Height(In Meter)
Basement 2	PARKING	3.8000	PARKING	3.8000	PARKING	3.8000
Basement 1	PARKING	3.8000	PARKING	3.8000	PARKING	3.8000
Hollow Plinth/Ground Floor	PARKING	4.1000	PARKING	4.1000	PARKING + COMM	4.1000
Floor 1	RESI.	3.6500	RESI.	3.6500	COMM + RESI	3.6500
Floor 2	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 3	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 4	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 5	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 6	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 7	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 8	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 9	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 10	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 11	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 12	RESI.	3.1000	RESI.	3.1000	RESI	3.1000
Floor 13	RESI.	3.1000	RESI.	3.1000	RESI	3.1000

Ramp only permitted for 18 to 25 meters building in margin.

Basic Fire Requirement Notes on plan

Take online print of approved opinion and submitted plan copy .The copies of plans are provide during final

inspection of the fire fighting system.

After, the building is built and all the required Fire safety and Protection equipment have been installed and after due inspection by the Fire service officer an NOC can be issued.

**Note : if plans are submitted for only industrial building approval, Industrial Building -
Information about all processes, raw material and finished material shall be mentioned in plan.**



A handwritten signature in blue ink, appearing to read "M.F. Dastoor".

(M.F.Dastoor)

Chief Fire Officer