

SPECIFICATIONS

- 3 SIDE OPEN APARTMENTS WITH MINIMAL COMMON WALL CONCEPT
- TWO APARTMENTS PER FLOOR
- EARTHQUAKE RESISTANT STRUCTURE
- BRICKS PARTITION WALL WITH MALA PLASTER AND BIRLA WHITE PUTTY FINISH
- EXTERIOR PLASTER-DOUBLE COAT WITH TEXTURE FINISH AND ACRYLIC PAINT
- POWDER COATED ALUMINUM SLIDING WINDOWS WITH FLY MASH/MOSQUITO SHUTTER AND SAFETY GRILL
- 3-PHASE CONCEALED COPPER WIRING WITH MODULAR SWITCHES AND MCB & ELCB
- FLOORING-GLAZED VITRIFIED TILES(GVT) IN ALL ROOMS
- TILES – GVT VITRIFIED TILES DADO AND FLOOR
- KITCHEN – BLACK GRANITE PLATFORM WITH S.S. SINK AND GVT TILES DADO
- WOODEN DOOR FRAMES WITH LAMINATED FLUSH DOORS
- ELEVATOR – OMEGA AUTO LIFT WITH GLASS DOORS AND S.S. CABIN
- TERRACE & PARKING – VITRIFIED FLOORING
- FIRE SAFETY AND SOLAR PANEL INSTALLATION AS PER NORMS